



IMPOX Filler

Product Information

Description:

A specially formulated, three components high build epoxy resin, it is used to restore the structural integrity of concrete, where static cracks and holes have appeared. It is known for its high strength, strong adhesion, and impact resistance.

Chemical Specifications:

Color:	Some RAL colors
Code:	057
Density:	1.95 Kg/l.
Binder:	Epoxy resin
Flash point:	flammable.
Solid content:	72%
Adhesion power:	Excellent.

Application Methods:

Application:	By steel trowel or knife
Drying time:	Touch dry : 20 minutes. Hard : Over night
Coverage:	1.95kg/m ² for 1 mm thickness
Packaging:	In pails of 25kg
Pot Life:	2 hours at a 20°C

General Surface Preparation:

The surfaces must be sound, clean, free from grease, oil, dirt, mildew or any curing compound.

The substrate should be primed with our IMPOX primer

Precautions and safety:

- This product must be shelved under normal conditions, hence, keep from freezing.
- In case of eye contact, wash thoroughly with water.
- Do not take internally. If swallowed seek medical assistance directly. Do not induce vomiting.
- Keep out of reach of children.

TONACO®

Supplied by Supremelogic limited . New House . Church Road
Llanishen Chepstow . Monmouthshire NP16 6QS UK
Telephone: 01600 860117 . Facsimile: 01600 869075
E-mail: anis@supremelogic.co.uk