

**OVER LINE GLOSS**  
**<Product Information>**

---

<b>PRODUCT CODE</b>	<b>: 311.0114</b>
<b>PACKAGING TYPE</b>	<b>: 2,5 LT - 7,5 LT- 15 LT</b>
<b>COLORS</b>	<b>: See color catalogue</b>
<b>DESCRIPTION</b>	<b>: Acrylic emulsion based ready for use silky gloss protective and decorative interior final. The acrylic binders strength is modified with special chemicals to provide water reppelling, dust resistant, easy wiping qualities.</b>
<b>FIELDS OF USE</b>	<b>: Used on interior wall surfaces prepared with various pastes.</b>
<b>PROPERTIES</b>	<b>:</b> <ul style="list-style-type: none"><li>• Antifungal and antibacterial.</li><li>• Does not hold dust, dirt or grease.</li><li>• Can be wiped.</li><li>• Silky gloss.</li><li>• Covering.</li><li>• Spreads well.</li><li>• Breathes.</li><li>• Ready for use.</li></ul>

---

**TECHNICAL PROPERTIES :**

<b>Appearance</b>	<b>: Silky gloss, flat appearance.</b>
<b>Chemical Composition</b>	<b>: Modified – acrylic emulsion based</b>
<b>Solid Matter (Weight)</b>	<b>: 53-56% (Values are approximate and may vary for different colors)</b>
<b>Solid Matter (Volume)</b>	<b>: 41-45% (Values are approximate and may vary for different colors)</b>
<b><u>Density (Kg/m<sup>3</sup>)</u></b>	<b>: 1,25 ± 0,03</b>
<b>Viscosity (KU/25°C)</b>	<b>: 85 - 95</b>
<b>Gloss</b>	<b>: 60 ° 30 ± 5</b>

<b>Recommended number of layers</b>	:	Usually <b>2 layers</b> (More layers might need to be applied depending on the surface)
<b>Recommended application tools:</b>		Roller and brush
<b>Drying time</b>	:	Final dry, 24 hours
<b>( 20oC, %60 RH )</b>		2nd layer application time, at least 6 hours
<b>Dilution ratio</b>	:	Do not dilute. If necessary dilute with %5 water. (20 parts paint 1 part water)
<b>Consumption</b>	:	In one layer 50 – 90 ml / m <sup>2</sup> or In one layer 70 - 120 gr /m <sup>2</sup>
<b>Packaging Amount</b>	:	2,5 lt sufficient for about 12 m <sup>2</sup> (varies depending on the surface)
<b>(2 layers applied)</b>		7,5 lt sufficient for about 40 m <sup>2</sup> (varies depending on the surface) 15 lt sufficient for about 80 m <sup>2</sup> (varies depending on the surface)

---

## **SURFACE PREPARATION :**

### **Newly Painted Surfaces :**

- Surface should be cleaned by sanding (big plaster pieces and naps removed).
- Free dust and grease on the surface should be cleaned by washing, brushing etc.
- One of the above recommended primers should be used according to the surface (As described in the technical manual or product packaging).
- When paint is applied over plaster, or chalky painting was done on the surface or there is chalk in the plaster:

Free chalk should be removed by quenching/washing with a brush etc.

Chalk that cannot be removed is reduced by washing the surface with a mix of 1 part household hydrochloric acid and 5 parts water. Dried surface is ready for paint or primer.

Alternatively, 1 or 2 layers of **Overline primer recommended for chalky surfaces and/or plasters** could be used. Paint can be applied at least a day after the primer.

## **Old, Painted Surfaces :**

- 1. Cracked, loose paint is cleaned and the surface is leveled with necessary plastering.**
  - Plastered areas are leveled. A layer of **Over Line primer** is applied to the whole surface.
  - At least 6 hours after, the primer is ready for the paint.
- 2. Painting over firm, undamaged paint.**
  - Surface is slightly sanded, **Over Line** the paint itself is used as primer.
  - Regardless, primer is applied in one layer.
  - At least 6 hours after primer paint can be used.
- 3. Solvent based satin painted.**
  - Slightly sand the surface and soften it with Over Line S-primer (roll over the same place slowly and repeatedly) and before it dries completely use a 1. layer water-based primer or final.

---

## **APPLICATION :**

- Over Line Glossy should be used on properly prepared, clean, dry, dust free surfaces.
- Paint must be stirred homogenously in its original packaging and not diluted. Dilute with 5 % water at most if necessary (Due to the surface condition, climate, etc.).
- Use Over Line Glossy in 2 or 3 layers. Wait at least 6 hours between application layers. Applications with 1 day intervals are more durable.

## **IMPORTANT NOTES ON APPLICATION :**

- The surface should be properly prepared.
- Paint should be stirred well before use.
- Should not be applied under +5 °C or + 35 °C.
- The waiting time between layers should be observed.

**CLEANING APPLICATION TOOLS :**

- Wash with cold water
- Or put in cold water.

**STORAGE :** Can be stored for at least 2 years in closed, protected environments in original packaging if protected from frost and sunlight..

**SAFETY PHRASES :**

- S 2** Keep out of the reach of children.
- S7** Keep with the lid tightly sealed.
- S26** On contact with eyes wash with plenty of water and consult a physician.
-