

OVERLINE SILICON MAT

<Product Information>

| | |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PRODUCT CODE | : 311.0113 |
| PACKAGING TYPE | : 2,5 LT - 7,5 LT- 15 LT |
| COLORS | : See color catalogue |
| DESCRIPTION | : Due to strong qualities of silicon and acrylic binder, excellent protector, decorative, silky matt interior final. |
| FIELDS OF USE | : Used on interior wall surfaces prepared with various pastes. |
| PROPERTIES | : <ul style="list-style-type: none">• Antifungal and antibacterial.• Does not hold dust, dirt or grease.• Can be wiped.• Silky Matt.• Covering.• Spreads well.• Breathes.• Ready for use. |

| | |
|------------------------------------------|----------------------------------------------------------------------------|
| TECHNICAL PROPERTIES | : |
| Appearance | : Silky matte, flat appearance. |
| Chemical Composition | : Silicon – acrylic emulsion based |
| VOC | : 35 G/L |
| Solid Matter (Weight) | : 55-58% (Values are approximate and may vary for different colors) |
| Solid Matter (Volume) | : 41-45% (Values are approximate and may vary for different colors) |
| <u>Density (Kg/m³)</u> | : 1,30 ± 0,03 |
| Viscosity (KU/25°C) | : 118 - 128 |
| Gloss | : 85 ° 45 ± 3 |

| | |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recommended number of layers | : Usually 2 layers (More layers might need to be applied depending on the surface) |
| Recommended application tools: | Roller and brush |
| Drying time | : Final dry, 24 hours |
| (20°C, %60 RH) | 2nd layer application time, at least 6 hours |
| Dilution ratio | : If necessary dilute with 10% water. (20 parts paint 2 parts water) |
| Consumption | : In one layer 50 – 90 ml / m ² or In one layer 70 - 120 gr /m ² |
| Packaging Amount | : 2,5 lt sufficient for about 12 m ² (varies depending on the surface) |
| (2 layers applied) | 7,5 lt sufficient for about 40 m ² (varies depending on the surface) 15 lt sufficient for about 80 m ² (varies depending on the surface) |

SURFACE PREPARATION :

Newly Painted Surfaces :

- Surface should be cleaned by sanding (big plaster pieces and naps removed).
- Free dust and grease on the surface should be cleaned by washing, brushing etc.
- When OVERLINE is applied over wood, OVERLINE-S primer should be used.
- When OVERLINE is applied over plaster, or chalky painting was done on the surface or there is chalk in the plaster:

Free chalk should be removed by quenching/washing with a brush etc.

Chalk that cannot be removed is reduced by washing the surface with a mix of 1 part household hydrochloric acid and 5 parts water. Dried surface is ready for paint or primer.

Alternatively, 1 or 2 layers of **Overline primer recommended for chalky surfaces and/or plasters** could be used. Paint can be applied at least a day after the primer.

Old, Painted Surfaces :

1. **Cracked, loose paint is cleaned and the surface is leveled with necessary plastering.**
 - Plastered areas are leveled. A layer of **Over Line primer** is applied to the whole surface.
 - At least 6 hours after, the primer is ready for the paint.
 2. **Painting over firm, undamaged paint.**
 - Surface is slightly sanded, a layer of **Over Line primer** is used or the paint itself is used as primer.
 - Regardless, primer is applied in one layer.
 - At least 6 hours after primer paint can be used.
 3. **Solvent based satin painted.**
 - Slightly sand the surface and soften it with Over Line solvent base primer (roll over the same place slowly and repeatedly)
-

APPLICATION :

- Over Line Silky Mat should be used on properly prepared, clean, dry, dust free surfaces.
- Paint must be stirred homogenously in its original packaging and not diluted. Dilute with 5 - 10 % water at most if necessary (Due to the surface condition, climate, etc.).
- Use Over Line Silky Mat in 2 or 3 layers. Wait at least 6 hours between application layers. Applications with 1 day intervals are more durable.

IMPORTANT NOTES ON APPLICATION :

- The surface should be properly prepared.
- Paint should be stirred well before use.
- Dilute in the shown amount.
- Should not be applied under +5 °C or + 35 °C.
- The waiting time between layers should be observed.

CLEANING APPLICATION TOOLS :

- Wash with cold water
- Or put in cold water.

STORAGE : Can be stored for at least 2 years in closed, protected environments in original packaging if protected from frost and sunlight..

SAFETY PHRASES :

- S 2** Keep out of the reach of children.
- S7** Keep with the lid tightly sealed.
- S26** On contact with eyes wash with plenty of water and consult a physician.
-