# **OVERLINE E-primer** <**Product Information**>

PRODUCT CODE : 311.0203

**PACKAGING TYPE** : 2,5 LT – 15 LT

**COLORS** : Milky white

**DESCRIPTION** : Modified acrylic emulsion based transparent surfaces fixing primer.

FIELDS OF USE : Use on newly painted plastered and/or satin plastered wall surfaces to fix and

bind plaster dust.

PROPERTIES :

• Ready for use (do not dilute).

• Low VOC

• Especially good for interiors.

• Binds dust.

• Reduces final absorption.

Increases final adhesion.

Easy to apply.

**TECHNICAL PROPERTIES**:

**Appearance** : Milky white

**Chemical Composition** : Acrylic based

**VOC** : 12G/L

**Solid Matter (Weight)** : 22%

**Solid Matter (Volume)** : 18%

<u>Density (Kg/m<sup>3</sup>)</u> :  $1 \pm 0.02$ 

**Viscosity**  $(KU/25^{\circ}C)$  : 50 - 60

**Diluter** : Do not dilute.

**Recommended application** 

**Number of layers** : Single layer.

**Drying time** : Final dry, 24 hours

(20oC, %60 RH) Time to apply paint, at least 6 hours

Recommended application tools: Brush and roller

**Recommended Finals**: All finals and primers that can be diluted with water.

**Consumption** : In one layer  $30 - 70 \text{ ml} / \text{m}^2$  (varies with surface, absorption)

In one layer  $30 - 70 \text{ gr} / \text{m}^2$  (varies with surface, absorption)

**Packaging Amount** : 2,5 lt sufficient for about 30 m<sup>2</sup>(varies depending on the surface)

(Single layer applied) 15 lt sufficient for about 200 m<sup>2</sup> (varies depending on the surface)

#### **SURFACE PREPARATION** :

## **Newly Painted Surfaces**:

• Level plastered, pasted, and satin plastered surfaces by sanding.

- Remove sanding dust.
- Surface must be clean, dust free and dry.
- Surface is ready for OVER LINE E-primer after this.

### APPLICATION

- Stir in packaging.
- Do not dilute.
- Can be colored slighly with %5 color paste
- Do not color with paint.
- Apply to dry, clean, dust free surface.
- Apply with roller in one layer.
- Use final 6 hours after application.

## IMPORTANT NOTES ON APPLICATION

- The surface should be properly prepared.
- Should be stirred well before use.
- Do not dilute.
- Do not add paint or primer.
- Color with at most 5% color paste if desired.

## **CLEANING APPLICATION TOOLS:**

- First use plenty of cold water.
- If needed hot water afterwards.

**STORAGE**: Can be stored for at least 2 years in closed, protected environments in original packaging if protected from frost and sunlight.

## SAFETY PHRASES

**S 2** Keep out of the reach of children.

:

- **S7** Keep with the lid tightly sealed.
- S26 On contact with eyes wash with plenty of water and consult a physician.