

OVERLINE P-primer

PRODUCT CODE	: 311.0201
PACKAGING TYPE	: 2,5 LT – 15 LT
COLORS	: Standard pure color CRACKED WHITE.
DESCRIPTION	: Acrylic emulsion based, protective, pigmented interior primer with silicon that reduces final consumption.
FIELDS OF USE	: Use on new mineral surfaces (plastered) or old surfaces painted with water based paints as primer.
PROPERTIES	: <ul style="list-style-type: none">• White and covering.• Pigmented.• Adheres well.• Use with water diluted paints.• Reduces final consumption.

TECHNICAL PROPERTIES :

Appearance	:	Matt cracked white.
Chemical Composition	:	Acrylic based
VOC	:	52G/L
Solid Matter (Weight)	:	67-69%
Solid Matter (Volume)	:	45-49%
<u>Density (Kg/m³)</u>	:	1,65 ± 0,02
Viscosity (KU/25°C)	:	118 - 128
Diluter	:	Water.
Recommended application		
Number of layers	:	One layer is usually sufficient.
Drying time	:	Final dry, 24 hours
(20oC, %60 RH)		Time to apply paint, 2 hour

Recommended application tools: Brush and roller

Dilution Ratio : Dilute with 9 or 5 parts primer and 1 part water depending on absorption of the surface. (10-15%)

Recommended Finals : Over Line group of paints etc. water based interior finals.

Consumption : In one layer 50 – 80 ml / m² (varies with surface and application)
In one layer 80 – 130 gr / m² (varies with surface and application)

Packaging Amount : 2,5 lt sufficient for about 30 m² (varies depending on the surface)
(Single layer applied) 15 lt sufficient for about 180 m² (varies depending on the surface)

SURFACE PREPARATION :

Newly Painted Surfaces :

- Clean surface by sanding (remove large plaster remains).
- Remove free dust by washing, brushing etc. methods.
- **If there is no chalk in plaster or on surface;** apply 1 layer of Over Line P-Primer.
- **If there is chalk in plaster or on surface;**
 - Clean excess chalk by washing with a brush etc.
 - Wash the surface with a 20% household hydrochloric acid solution and clean water to reduce effect of remaining chalk. After the surface has dried, , wait 1 day, and apply 1 layer of Over Line P-primer.

NOTE : *Color stains on surfaces that were not properly cleaned of chalk or isolated will not be considered paint fault.*

Old, painted surfaces :

- Scratch the surface to remove loose paint.
- Make the necessary repairs and plastering.
- Repair unevenness. (By scratching and plastering)
- Apply Over Line P-primer in 1 layer to dry, clean, dust-free surface.

APPLICATION :

- 1.) Use Over Line P-primer on clean, dry, dust free surfaces after necessary preparation is done such as sanding, plastering and cleaning.
- 2.) Stir paint homogenously in original packaging before using and dilute in the described amount.
- 3.) Over Line is usually applied in one homogenous layer and at least 2 hours are allowed to pass after another Over Line group final can be applied.

IMPORTANT NOTES ON APPLICATION :

- The surface should be properly prepared.
- Paint should be stirred well before use.
- Must be diluted as recommended.
- Should not be applied under +5 °C or + 35 °C.
- The waiting time between layers should be observed.

CLEANING APPLICATION TOOLS :

- Immediately wash with cold water.
- Or leave in cold water.

STORAGE : Can be stored for at least 2 years in closed, protected environments in original package if protected from frost and sunlight.

SAFETY PHRASES:

- S 2** Keep out of the reach of children.
- S7** Keep with the lid tightly sealed.
- S26** On contact with eyes wash with plenty of water and consult a physician.