

# TONAFLEX-W

## <Product information>

**DESCRIPTION** : Acrylic copolymer emulsion based, flexible, ready for use exterior putty and surface leveling paste.

**FIELDS OF USE** : Used to cover concrete and plaster cracks and holes

**PROPERTIES** :

- Resistant to water, humidity and impact.
- Enables complete compatibility and adherence to the surface.
- Breathes.
- Reduces paint consumption.
- Covers drying cracks.
- Produces durable surfaces.

**TECHNICAL PROPERTIES** :

**Appearance** : Flat, matte appearance.

**Chemical Composition** : Acrylic copolymer based

**Solid Matter (Weight)** : (approximately) 82±1,5%

**Density (Kg/m<sup>3</sup>)** : 1,82 ± 0,03

**Diluter** : Ready for use, do not dilute.

**PACKAGING TYPE** : 4 KG – 23 KG

### **Recommended application**

**Number of layers** : Usually **1 or 2 layers** (Varies with surface condition)

**Drying time** : Full hardening, 24 hours

**( 20oC, %60 RH )** 2nd layer paint application time, approximately 24 hours

**Application tools** : Steel spatula

**Consumption** : Depending on porosity and absorption 0,5 – 1 kg / m<sup>2</sup>

## **SURFACE PREPARATION**

- Roughly sand the surface.
- Remove free dust, paint and grease.
- Slightly widen the cracks to prepare for pasting.

## **APPLICATION :**

- Use TONAFLEX-W on clean, dust-free surfaces.
- Stir homogenously in original packaging before use.
- TONAFLEX-W can be used in 1-2 or more layers. Wait at least 24 hours between layers.
- Apply in thin layers; do not apply more than 5 mm in a single layer
- For higher thickness, 200g of gray cement can be added for each 1kg of paste

## **IMPORTANT NOTES ON APPLICATION :**

- The surface should be properly prepared.
- Should not be applied under +5 °C or over +35 °C.
- Apply in thin layers, no thicker than 5 mm.
- Level the surface by sanding after application.
- The waiting time between layers should be observed.

## **CLEANING APPLICATION TOOLS : Water**

**STORAGE:** Can be stored for a maximum period of one year in original packaging if protected from frost and sunlight.

## **SAFETY PHRASES :**

- S 2** Keep out of the reach of children.
- S7** Keep with the lid tightly sealed.
- S26** On contact with eyes wash with plenty of water and consult a physician.