

# **TONAPATCH**

## **Product Information**

**Description:** A specially formulated, high resin flooring putty, it is used to restore the structural integrity of concrete, where static cracks and holes have appeared. It is known for its high strength, strong adhesion, impact and chemical resistance.

### **Chemical Specifications:**

<b>Color:</b>	Grey or some RAL colors
<b>Code:</b>	057
<b>Density:</b>	1.95 Kg/l.
<b>VOC :</b>	29G/L
<b>Binder:</b>	special resin
<b>Flash point:</b>	Non-flammable.
<b>Viscosity:</b>	High thixotropic.
<b>Solid content:</b>	80%
<b>Adhesion power:</b>	Excellent.

### **Application Methods:**

<b>Application:</b>	By steel trowel or knife
<b>Drying time:</b>	Touch dry : 20 minutes. Hard : Over night
<b>Coverage:</b>	1.95kg/m <sup>2</sup> for 1 mm thickness
<b>Packaging:</b>	In pails of 25kg

### **General Surface Preparation:**

The surfaces must be sound, clean, free from grease, oil, dirt, mildew or any curing compound.

### **Precautions and safety:**

- this product must be shelved under normal conditions, hence, keep from freezing.
- In case of eye contact, wash thoroughly with water.
- Do not take internally. If swallowed seek medical assistance directly. Do not induce vomiting.
- Do not transfer contents to unlabeled containers.
- Close container after each use.
- Keep out of reach of children.

