

POLIMEL/LUX

<Product Information>

Description:

A premium alkyd enamel that can be Matt,semi-gloss or glossy according to the client's request. This enamel can be used on interior walls, ceilings, wood or metal. It is highly recommended for heavy use areas of hospitals, schools, offices, and hotels because in such places a durable and washable low sheen finish is designed.

Chemical Specifications:

Color:	RAL
Density:	1.2-1.24 kg/l
Binder type:	Glycerophthalic resin
Flash point:	35 C
PVC:	26 %
Viscosity:	80-90 Ku's
Solid content:	57 %
Volatile:	43 %

Application method:

Number of coats:	two coats for maximum hiding and color uniformity.
Application:	By brush, roller, or spray gun
Coverage:	About 44 sqm per U.S gallon
Drying time:	Touch dry: 30 min Hard: overnight.
Packaging:	In tins of 2.5 or 7.5 liters In pails of 15 liters
Aspect:	Semi-gloss or Matt finish
Cleaning:	With white spirit or mineral spirit.
Thinner:	25% white spirit

General Surface Preparation:

All areas must be sound, dry, free of oil, grease or dirt, and peeling point. New surfaces should be primed with our undercoat, wait 24 hours, and then apply the finish enamel.

For previous painted surfaces, dull glossy areas by light sanding and dust. Remove loose paint, prime bare areas with appropriate primer. Fill cracks with suitable filler and then brush with the required enamel.

Precaution and Safety:

- Combustible. Keep away from heat, sparks, and open flame.
- When spraying, make sure of appropriate ventilation.
- Do not intake internally.
- Do not paint in damp, frosty or cold weather.
- Do not apply too heavily
- Close container after each use.
- Keep out of reach of children.